

1.22.15

PREPARED FOR:

Customer: Brink Farms Inc

Contact:

Brian Brink

## The Power of Teamwork





brianbrink@brinkfarms.com UTRC12215 We are pleased to submit for your consideration, 1 Used 2012 Trackmobile Titan with all standard equipment listed below.

Hours:

Phone: 269-751-5965

3,700

Fax:

9648M

Engine / Cummins QSB 6.7 /Tier III / 260 BHP @ 2500 RPM

Air Brake System / Railcar / 100 cfm

Air Cleaner / Donaldson Heavy-Duty / 2 Stage Filtration

Air Dryer / Trackmobile Air System

Air Ride Body Frame Suspension

Alternator / 160 Ampere

Automatic Engine Shutdown

Axles / Rail / Two (2) / Axle Tech PRLC

Batteries / Two (2) Each / 12 Volt / 925 CCA

Brakes

Parking / Spring Applied / Air Released Disc/Caliper Arrangement Rail-Mode / Four (4) 18 Inch Disc (457 Millimeters) Hydraulically

Road-Mode / Two (2) Drum & Shoe / Rear Road Wheel Axle

Cab / Operator's / 360 Degree Clear Vision / 75 inch Headroom

Camera / Rear Coupler Alignment

Control System / Digital Monitoring System / Network Multiplexed

Time & Date

Tachometer

Warning Lights

Transmission Direction & Gear

Transmission Oil Temperature

Monitors & Displays

Air Compressor Oil Temperature

**Battery Voltage** 

Diagnostics

Engine Coolant Temperature **Engine Hours** 

Engine Oil Pressure

Fuel Level

Fuel-Water Separator Warning

Speedometer

System Air Pressure

Couplers

Two (2) / Weight Transfer / Hydraulic Controlled

Air Operated, Electrically Controlled Knuckle Release

Cup Holders / Two

Defroster System / Operator's Cab / Front & Rear Windshield

Differential / Automatic No-Spin Locking

Doors / Operator's Cab / Two (2) / Front & Rear

Dual Terminal Accessory / Operator Console

Frame / Heavy-Duty / Two (2) Inch (51 Millimeters) Slab Steet

Fuel Tank / 50 Gallon (189 Liters) Capacity

Gauge / Air Brake System / Large Dual / Reservoir & Train Line Pressure

Heater / Air Intake / Cold Temperature Starting

Heater / Operator's Cab / Hot Water / Electric Fan Circulated

Horn / Warning / Air Blast

Hydraulic Lock-Out Switch

Hydraulic System / Constant Pressure With Engine Running

Lights

Email:

Cab / Interior / Dome / Two / (1) Clear & (1 Red

Rail-Mode & Road-Mode

Forward Direction / Three (3) Sealed Beam Halogen Lights

Reverse Direction / Three (3) Sealed Beam Halogen Lights

Rear / Two (2) Tail & Stop Combination Lights

Worklights / Two / Front Mounted, Top Of Cab

Mirror / Rear View / Road-Mode / Mounted Inside Cab

Muffler / Sound Attenuating

Platform / Rear Cross-Over

Power Steering / Road-Mode

Rail Wheels / 27 Inch (686 Millimeters) / Heat-Treated / Puncture Proof

Road Wheels / Rock Service /

Twenty (20) Ply / 12.00 x 20 / Heavy Duty Mine Service / Rubber Tires

Rotary-Screw Compressor / Maximum 100 CFM / 100% Duty Cycle /

Extended Service Intervals

Sanders / Eight (8) / Both Front & Rear Of All Rail Wheels / Air Operated,

Seat / Air Ride / 180 deg. Swivel for Operation in Either Direction /

Highback Railroad Seat / Adjustable / With Seatbelts

Arm Rest-Mounted Controls for:

Throttle, Sanders, Air Blast Horn, Coupler Knuckle Release,

Coupler Traverse, Coupler Raise & Lower, Service Brakes,

Transmission (Direction & Gear), Train Air Brake Control

Sound Suppression / Below 85 dba

Steps / Inclined / With Lights / For Use In Night Operations

Tilt-Away Steering Wheel

Transmission & Torque Converter

Funk DF Series / Electronically Controlled / Fully Automatic /

Four (4) Speed Forward & Reverse


Sun Visor / Front Window

Warning Alarm / Reverse Direction

Windshield Wipers & Washers / Two (2) / Front & Rear Windshields







•			
	7	1900	
			3

<ul><li>Tier</li></ul>		Electronic	Engine
------------------------	--	------------	--------

- Electronically controlled engine torque output
- CAN-Bus Control System & Onboard Diagnostic System
- Larger cab with controls integrated into seat
- 100 CFM Rotary Compressor
- Hydraulic rail and road brakes
- Trackmobile pioneered automatic transmission
- Work area video cameras

	TITAN DIMENSI	ONS	
	On rail AAR Clearance	On Road	
Wheel base	149.3"	82.5"	
Length	194.8"	194.8"	
Width	123.0*	123.0"	
Height	145.8"	156.8"	
Weight	50,850 LE		

Tractive Effe	
33,100 lbs	Single Coupled
49,500 lbs	Double Coupled

