

WHEEL MEASURE

Test Date: 1-24-23

POS.	FLANGE HEIGHT [LIMIT: 1 7/16"]	FLANGE THICKNESS [LIMIT: 1"]	RIM THICKNESS [LIMIT: 1 1/18"]	POS.	FLANGE HEIGHT [LIMIT: 1 7/16"]	FLANGE THICKNESS [LIMIT: 1"]	RIM THICKNESS [LIMIT: 1 1/18"]
L1	1 3/16"	1 7/64"	1 9/16"	R1	1 3/16"	1 7/64"	1 9/16"
L2	1 1/8"	1 7/64"	1 3/4"	R2	1 1/8"	1 7/64"	1 3/4"
L3	1 1/8"	1 7/64"	1 3/4"	R3	1 1/8"	1 7/64"	1 3/4"
L4	1 1/8"	1 7/64"	1 5/16"	R4	1 1/8"	1 7/64"	1 5/16"

Comments:

TOP OF RAIL CLEARANCE HEIGHT

COUPLER HEIGHT (MAX. 34 1/2" MIN. 32 1/2")		PILOT HEIGHT (MAX. 6" MIN. 4")		FLOOR HEIGHT (51 in ±1.0")	
FRONT	33 1/2"	FRONT	4 3/4"	1R	50 3/4"
REAR	33 1/2"			2R	51"
				1L	50 3/4"
				2L	50 1/2"

AIR SPRING VERIFICATION INSPECTION

AIR SPRING HEIGHT				AIR SPRING PRESSURE	NO. 1 END 70 LBS.
L1	9 1/4"	L2	9 1/8"		
R1	9"	R2	9 1/4"		

SINGLE CAR TEST PRESSURES

ASP		BCP	FULL SERVICE	EMERGENCY
DEFLATED	0	DEFLATED	62	76
AW0	67	AW0	64	77
AW3	85	AW3	72	89